

N° :

## DATASHEET

Date : 8 janv. 2021

### Universal drive IP20

Commander C200-05400300A10100AB100

### Definition

|                         |                                                                      |
|-------------------------|----------------------------------------------------------------------|
| Product range           | Commander                                                            |
| Model                   | C200-054-00300A                                                      |
| Model                   | 200 (1 SI option - CodeSys) 6 pulses - internal choke (A)            |
| Onboard Comms           | Optionnal comms (1 option slot)                                      |
| Onboard intelligence    | Machine Control Studio (IEC61131-3)                                  |
| Control Connections     | No STO / 2 AI (0-10V & 4-20mA) + 1 AO (0-10V) + 4 DI + 1 DIO + 1 RLY |
| Product cooling version | Air cooling (A)                                                      |



### Electrical characteristics

#### Network side electrical characteristics

|                                    |                               |
|------------------------------------|-------------------------------|
| Power supply number of phases      | 3                             |
| Power supply voltage and frequency | 380 to 480V (±10%) 45 to 66Hz |
| Power supply nominal current (A)   | 30.0                          |

#### Motion side electrical characteristics

#### Heavy duty / Open loop control mode

|                                                                |                      |
|----------------------------------------------------------------|----------------------|
| Continuous output current (A)                                  | 30.00 @ 3 kHz - 40°C |
| Output maximal current (A)                                     | 45.00                |
| Maximum overload duration from 100% Ico (s) / repetitivity (s) | 7.00 / 600.00        |
| Maximum overload duration from cold (s) / repetitivity (s)     | 60.00 / 600.00       |

| Power supply voltage (V ±10%) | Power supply number of phases | Power supply nominal current (A) | Overload    | Maximum ambient temperature (°C) | Switching frequency (kHz) | Continuous output current (A) | Losses (W) |
|-------------------------------|-------------------------------|----------------------------------|-------------|----------------------------------|---------------------------|-------------------------------|------------|
| 400                           | 3                             | 30.0                             | Heavy duty  | 40                               | 3                         | 30.0                          | 322        |
|                               |                               |                                  |             | 50                               | 3                         | 24.0                          | 264        |
|                               |                               |                                  | Normal duty | 40                               | 3                         | 31.0                          | 332        |
|                               |                               |                                  |             | 50                               | 3                         | 25.5                          | 280        |

| Power supply voltage (V ±10%) | Power supply number of phases | Surcharge   | Mode de fonctionnement | Output maximal current (40°C) (A) | Maximum overload duration from 100% Ico (s) | Maximum overload duration from cold (s) |
|-------------------------------|-------------------------------|-------------|------------------------|-----------------------------------|---------------------------------------------|-----------------------------------------|
| 400                           | 3                             | Heavy duty  | Open loop control mode | 45.0                              | 7.00                                        | 60.00                                   |
|                               |                               | Normal duty | Open loop control mode | 34.1                              | 9.00                                        | 165.00                                  |

### characteristics

|                    |                |                               |      |
|--------------------|----------------|-------------------------------|------|
| Size               | 05             | Drive flow rate (m3/h)        | 84   |
| Dimensions (HxWxD) | 365 x 143 x202 | accoustic noise (dB(A))       | 56.9 |
| Weight (kg)        | 7.40           | Maximal altitude (m)          | 1000 |
| Protection indice  | IP20           | Maximal relative humidity (%) | 95   |

PNEUTROL INTERNATIONAL LIMITED  
sales@pneutrol.com

UK OFFICE:  
5 CAULSIDE DRIVE, ANTRIM, BT41 2DU, NORTHERN IRELAND  
TEL: + 44 (0) 28 9448 1800, [www.pneutrol.com/industrialspares](http://www.pneutrol.com/industrialspares)

EUROPEAN OFFICE:  
UNIT 6, ST ANTHONY'S BUSINESS PARK DUBLIN, D22 VW95, IRELAND,  
TEL: +353 (1) 437 3653, [www.pneutrol.com/industrialspares](http://www.pneutrol.com/industrialspares)

The information contained in this data-sheet is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as our compagny have an ongoing process of development and reserve the right to change the specification of their products without notice.  
Control Techniques Limited. Registered Office: The Gro, Newtown, Powys SY16 3BE. Registered in England and Wales. Company Reg. No. 01236886.  
Moteurs Leroy-Somer SAS. Headquarters: Bd Marcellin Leroy, CS 10015, 16915 Angoulême Cedex 9, France. Share Capital: 65 800 512 €, RCS Angoulême 338 567 258.

Version V8.305

## DATASHEET

N° :

Date : 8 janv. 2021

Universal drive IP20 - Commander C200-05400300A10100AB100

### Power options, network side

| Line choke | - | In (A) | Inductance (mH) | Losses (W) | Dimensions (HxWxD) | Weight (kg) |
|------------|---|--------|-----------------|------------|--------------------|-------------|
|            |   | 0      | 0               | 0          | 0 x 0 x 0          | 0.0         |

### Power options, motion side

Braking transistor **Braking transistor Included**

### Integral options

|                                            |                                                   |
|--------------------------------------------|---------------------------------------------------|
| Integrated control interface               | Local controls and access to the basic parameters |
| HMI / keypad                               | -                                                 |
| PC communication interface                 | -                                                 |
| Option slot SM/SI 1                        | -                                                 |
| Option slot SM/SI 2                        | -                                                 |
| Option slot SM/SI 3                        | -                                                 |
| AI Option / Smartcard slot                 | -                                                 |
| HD15 / terminals feedback device interface | -                                                 |

### Environmental options

|                              |   |
|------------------------------|---|
| IP / UL / through panel kits | - |
| Product fan management       | - |

PNEUTROL INTERNATIONAL LIMITED  
sales@pneutrol.com

UK OFFICE:  
5 CAULSIDE DRIVE, ANTRIM, BT41 2DU, NORTHERN IRELAND  
TEL: + 44 (0) 28 9448 1800, [www.pneutrol.com/industrialspares](http://www.pneutrol.com/industrialspares)

EUROPEAN OFFICE:  
UNIT 6, ST ANTHONY'S BUSINESS PARK DUBLIN, D22 VW95, IRELAND,  
TEL: +353 (1) 437 3653, [www.pneutrol.com/industrialspares](http://www.pneutrol.com/industrialspares)

Version V8.305


The information contained in this data-sheet is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as our compagny have an ongoing process of development and reserve the right to change the specification of their products without notice.  
Control Techniques Limited. Registered Office: The Gro, Newtown, Powys SY16 3BE. Registered in England and Wales. Company Reg. No. 01236886.  
Moteurs Leroy-Somer SAS. Headquarters: Bd Marcellin Leroy, CS 10015, 16915 Angoulême Cedex 9, France. Share Capital: 65 800 512 €, RCS Angoulême 338 567 258.

DATASHEET

N° :

Date : 8 janv. 2021

Variable speed drive (6 pulses) : Commander C200-05400300A10100AB100



|         |     |
|---------|-----|
| H (mm)  | 365 |
| H1 (mm) | 391 |
| H2 (mm) | 0   |

|        |     |
|--------|-----|
| L (mm) | 143 |
|--------|-----|

|         |     |
|---------|-----|
| P (mm)  | 202 |
| P1 (mm) | 0   |

|                   |      |
|-------------------|------|
| Weight (kg)       | 7.40 |
| Total weight (kg) | 7.40 |

PNEUTROL INTERNATIONAL LIMITED  
sales@pneutrol.com

UK OFFICE:  
5 CAULSIDE DRIVE, ANTRIM, BT41 2DU, NORTHERN IRELAND  
TEL: + 44 (0) 28 9448 1800, [www.pneutrol.com/industrialspares](http://www.pneutrol.com/industrialspares)

EUROPEAN OFFICE:  
UNIT 6, ST ANTHONY'S BUSINESS PARK DUBLIN, D22 VW95, IRELAND,  
TEL: +353 (1) 437 3653, [www.pneutrol.com/industrialspares](http://www.pneutrol.com/industrialspares)