

N° :

## DATASHEET

Date : 19 janv. 2021

### Universal drive IP20 with options

Unidrive M400-06400470A10100AB100

keypad ;

### Definition

Product range	Unidrive
Model	M400-064-00470A
Model	400 (2 STO - 1 SI option - CodeSys) 6 pulses - internal choke (A)
Onboard Comms	Optionnal comms (1 option slot)
Onboard intelligence	Machine Control Studio (IEC61131-3)
Control Connections	2 STO / 2 AI (0-10V & 4-20mA) + 2 AO (0-10V & 4-20mA) + 5 DI + 2 DIO + 1 RLY
Product cooling version	Air cooling (A)



### Electrical characteristics

#### Network side electrical characteristics

Power supply number of phases	3
Power supply voltage and frequency	380 to 480V (±10%) 45 to 66Hz
Power supply nominal current (A)	60.0

#### Motion side electrical characteristics

#### Heavy duty / Open loop control mode

Continuous output current (A)	46.00 @ 3 kHz - 40°C
Output maximal current (A)	70.50
Maximum overload duration from 100% Ico (s) / repetitivity (s)	7.00 / 600.00
Maximum overload duration from cold (s) / repetitivity (s)	60.00 / 600.00

Power supply voltage (V ±10%)	Power supply number of phases	Power supply nominal current (A)	Overload	Maximum ambient temperature (°C)	Switching frequency (kHz)	Continuous output current (A)	Losses (W)
400	3	60.0	Heavy duty	40	3	46.0	496
				50	3	42.0	455
			Normal duty	40	3	63.0	656
				50	3	58.0	613

Power supply voltage (V ±10%)	Power supply number of phases	Surcharge	Mode de fonctionnement	Output maximal current (40°C) (A)	Maximum overload duration from 100% Ico (s)	Maximum overload duration from cold (s)
400	3	Heavy duty	Open loop control mode	70.5	7.00	60.00
		Normal duty	Open loop control mode	69.3	9.00	165.00

### characteristics

Size	06	Drive flow rate (m3/h)	130
Dimensions (HxWxD)	365 x 210 x227	acoustic noise (dB(A))	55.6
Weight (kg)	14.00	Maximal altitude (m)	1000
Protection indice	IP20	Maximal relative humidity (%)	95

PNEUTROL INTERNATIONAL LIMITED  
sales@pneutrol.com

UK OFFICE:  
5 CAULSIDE DRIVE, ANTRIM, BT41 2DU, NORTHERN IRELAND  
TEL: + 44 (0) 28 9448 1800, www.pneutrol.com/industrialspares

EUROPEAN OFFICE:  
UNIT 6, ST ANTHONY'S BUSINESS PARK DUBLIN, D22 VW95, IRELAND,  
TEL: +353 (1) 437 3653, www.pneutrol.com/industrialspares

## DATASHEET

N° :

Date : 19 janv. 2021

Universal drive IP20 with options - Unidrive M400-06400470A10100AB100

### Power options, network side

Line choke	In (A)	Inductance (mH)	Losses (W)	Dimensions (HxWxD)	Weight (kg)
-	0	0	0	0 x 0 x 0	0.0

### Power options, motion side

Braking transistor **Braking transistor Included**

### Integral options

Integrated control interface	Without display and setting
HMI / keypad	CI-KEYPAD LCD
PC communication interface	-
Option slot SM/SI 1	-
Option slot SM/SI 2	-
Option slot SM/SI 3	-
AI Option / Smartcard slot	-
HD15 / terminals feedback device interface	-

### Environmental options

IP / UL / through panel kits	-
Product fan management	-

PNEUTROL INTERNATIONAL LIMITED  
sales@pneutrol.com

UK OFFICE:  
5 CAULSIDE DRIVE, ANTRIM, BT41 2DU, NORTHERN IRELAND  
TEL: + 44 (0) 28 9448 1800, www.pneutrol.com/industrialspares

EUROPEAN OFFICE:  
UNIT 6, ST ANTHONY'S BUSINESS PARK DUBLIN, D22 VV95, IRELAND,  
TEL: +353 (1) 437 3653, www.pneutrol.com/industrialspares

Version V8.305



*The information contained in this data-sheet is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as our compagny have an ongoing process of development and reserve the right to change the specification of their products without notice.*  
Control Techniques Limited. Registered Office: The Gro, Newtown, Powys SY16 3BE. Registered in England and Wales. Company Reg. No. 01236886.  
Moteurs Leroy-Somer SAS. Headquarters: Bd Marcellin Leroy, CS 10015, 16915 Angoulême Cedex 9, France. Share Capital: 65 800 512 €, RCS Angoulême 338 567 258.

## DATASHEET

N° :

Date : 19 janv. 2021

Variable speed drive (6 pulses) : Unidrive M400-06400470A10100AB100



H (mm)	365
H1 (mm)	391
H2 (mm)	0

L (mm)	210
--------	-----

P (mm)	227
P1 (mm)	0

Weight (kg)	14.00
Total weight (kg)	14.15

PNEUTROL INTERNATIONAL LIMITED  
sales@pneutrol.com

UK OFFICE:  
5 CAULSIDE DRIVE, ANTRIM, BT41 2DU, NORTHERN IRELAND  
TEL: + 44 (0) 28 9448 1800, www.pneutrol.com/industrialspares

EUROPEAN OFFICE:  
UNIT 6, ST ANTHONY'S BUSINESS PARK DUBLIN, D22 VV95, IRELAND,  
TEL: +353 (1) 437 3653, www.pneutrol.com/industrialspares

Version V8.305

The information contained in this data-sheet is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as our compagny have an ongoing process of development and reserve the right to change the specification of their products without notice.

Control Techniques Limited. Registered Office: The Gro, Newtown, Powys SY16 3BE. Registered in England and Wales. Company Reg. No. 01236886.  
Moteurs Leroy-Somer SAS. Headquarters: Bd Marcellin Leroy, CS 10015, 16915 Angoulême Cedex 9, France. Share Capital: 65 800 512 €, RCS Angoulême 338 567 258.