



# ht range

## Oil Free Air Compressors

ultra low noise





- Ultra Quiet running, from just 53 dB(A)
- 100% Oil Free Design
- Efficient, Horizontal Twin pump unit
- Outlet Pressure Regulator fitted as standard
- Innovative Compact Design, perfect for limited space

This ground-breaking range is ideal for those applications where low maintenance and ultra quiet, oil free air is essential; scientific instruments, door controls, autoclave locks, stapling, picture framing and as a portable and rugged air supply for many diverse requirements. Available with 2 pole motor option delivering higher output with only a marginal increase in noise level – these models denoted 2P.

Model	HT3	HT3-2P	HT15	HT15-2P	HT24	HT24-2P
RPM	1400	2800	1400	2800	1400	2800
Kw HP	0.55 / 0.75	0.55 / 0.75	0.55 / 0.75	0.55 / 0.75	0.55 / 0.75	0.55 / 0.75
Volts/Hz	220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50	220-240 / 50
Bar	8	10	8	10	8	10
Ltrs	3	3	15	15	24	24
L/Min	103	144	103	144	103	144
1 Bar	79	130	79	130	79	130
2 Bar	68	116	68	116	68	116
3 Bar	59	104	59	104	59	104
4 Bar	51	93	51	93	51	93
5 Bar	42	82	42	82	42	82
6 Bar	36	73	36	73	36	73
7 Bar	31	70	31	70	31	70
8 Bar	27	65	27	65	27	65
dB(A)	53	59	53	59	53	59
KG	10	10	14	14	15	15
CM-hxwxh	26x23x43	26x23x43	55x37x37	55x37x37	53x40x40	53x40x40