


DESCRIPTION

Pilot-Operated Check Valve. Check valves operate on slight differential pressure. Free flow is permitted in the direction of the arrow, positive check in the opposite direction. Reverse flow can be achieved by reaching the required pilot pressure at port (3).



- **For hydraulic applications only**
- **Air pilot valves have secondary seal on pilot piston stem.**
A vent hole in the body between the piston seal and stem seal prevents mixing of pilot media and the system media



SPECIFICATIONS

Maximum Operating Pressure

Carbon Steel: 3,000 psi (207 bar)

Operating Temperature Range

Buna-N: -30° to +200° F (-34° to +93° C)

Maximum Recommended Flow

6.0 to 12.0 gpm (22.7 to 45.4 lpm)

Pilot Ratio

- 4:1 Hydraulic Pilot
- 2:1 Hydraulic Pilot under 90 psi (6 bar)
- 2:1 Air Pilot


Threads

NPTF, BSPT

Materials

Body: Steel
 Adapter: Steel
 O-Rings: Buna-N (PIC, PIDC)
 Viton (APIDC)
 Piston: Steel
 Piston Spring: Music wire
 Check Spring: Stainless Steel 302
 Piston Seals: Teflon (PIC, PIDC)
 Viton (APIDC)
 Teflon Back-up Washer (APIDC)
 Ball: Stainless Steel 440
 Ball Guide: Delrin®
 Washer: Stainless Steel 304
 Retainer Ring: Steel

INSTALLATION DIMENSIONS



Pipe Size	A HEX	B	C	D orifice	Pilot Port	Inlet Port	Outlet Port
1/4"	1-1/8 (28.6)	4-1/8 (104.8)	1-27/32 (43.7)	.281 (7.1)	1/4"	1/4"	1/4"
3/8"	1-3/8 (34.9)	4-7/8 (123.8)	2-1/8 (54.0)	.328 (8.3)	1/4"	3/8"	3/8"
1/2"	1-5/8 (41.3)	5-5/8 (142.9)	2-7/16 (61.9)	.359 (9.1)	1/4"	1/2"	1/2"

() Parentheses = Millimeters

Pneutrol International Limited

UK Office
 5 Caulside Drive, Antrim, BT41 2DU
 United Kingdom
 TEL: +44 (0) 28 9448 1800
www.pneutrol.com/industrialspares

HOW TO ORDER

NPTF Thread			
Size	Air Pilot	Hydraulic Pilot	Max. Flow gpm (lpm)
1/4"	—	PIC20S	6.0 (22.7)
3/8"	—	PIDC25S	10.0 (37.9)
1/2"	APIDC30S	PIDC30S	12.0 (45.4)

ISO 7/1 – RS BSP Taper Thread		
Size	Hydraulic Pilot	Max. Flow gpm (lpm)
1/4"	PICB20S	6.0 (22.7)
3/8"	PICB25S	10.0 (37.9)

sales@pneutrol.com

European Office
 Unit 6, Saint Anthony's Business Park, Ballymount Road, D22 VW95
 Ireland
 TEL: +353 (0) 1 4373653
www.pneutrol.com/industrialspares