


DFR-120-3

Fixed, Bypass-Type, Pressure-Compensated
Flow Regulator Valve



SERIES 12



DESCRIPTION

A fixed bypass-type cartridge valve designed to regulate priority flow while bypassing excess flow regardless of load pressure.

OPERATION

The DFR-120-3 maintains a constant flow within specified accuracies from ① to ③ regardless of downstream load pressure at ③ or bypass leg ②. When flow produces a minimum predetermined pressure differential across the compensator spool control orifice, the spool shifts against the spring force to throttle the flow and maintain the priority flow setting. Reverse flow is not regulated.

FEATURES and BENEFITS

- Pressure-compensated.
- Quiet response.
- Bypass port ② may be fully pressurized.
- Industry common cavity.

SPECIFICATIONS

Operating Pressure: 3000 PSI (207 Bar)

Flow: Ranges from 2 to 13 gpm (7.6 to 49.2 L/min.)
25 gpm (94.6 L/min.) max. input.
(See ordering table)

Flow Tolerances: Flows up to and including
3.0 gpm (11.4 L/min.) $\pm 15\%$
Flows over 3.0 gpm (11.4 L/min.) $\pm 10\%$

Temperature: -30°F to $+250^{\circ}\text{F}$ (-35°C to $+120^{\circ}\text{C}$)


Recommended Filtration: ISO 17/15/13

Fluids: Mineral-based fluids.


For other fluid compatibility consult factory.

Cavity/Cavity Tool: 120-3, see page 11.12.3

PRESSURE DROP VS. FLOW



DIMENSIONS Inches [Millimeters]



HOW TO ORDER

DFR	-	120	-	3	-	*	-	***
Flow Regulator Valve (Fixed)		Cavity		Flow Path		Seals		Flow

Seals		Seal Kit
N	Buna N	
V	Viton	

Flow - Nominal†	
200	2.00 gpm (7.57 lpm)
225	2.25 gpm (8.52 lpm)
250	2.50 gpm (9.46 lpm)
300	3.00 gpm (11.36 lpm)
360	3.60 gpm (13.63 lpm)
400	4.00 gpm (15.14 lpm)
500	5.00 gpm (18.93 lpm)
600	6.00 gpm (22.71 lpm)
1000	10.00 gpm (37.85 lpm)
1300	13.00 gpm (49.21 lpm)

† Other options available – consult factory

All variations may not be configurable. Minimum order quantities may be required on other models. Contact Deltrol Fluid Products for complete details.