

Pneu-Trol[®]


GS20 Gauge Snubber Male-to-Female

IN-LINE

DESCRIPTION

The Gauge Snubber is a fixed pressure valve which protects your gauges and other delicate instruments from hydraulic shock, pressure surges and pulsation. Its restrictive orifice provides rapid and smooth response to pressures up to 5,000 psi (345 bar).

• Protects gauges and other delicate instruments from shock pressure surges and pulsations





SPECIFICATIONS

Maximum Operating Pressure (Non-Shock Service) Brass: 2,000 psi (138 bar) Carbon Steel: 5,000 psi (345 bar)


Operating Temperature Range -30° to $+400^{\circ}$ F $(-34^{\circ}$ to $+204^{\circ}$ C)

Threads NPTF 1/4"

Orifice Diameter .015 (.38)

Material Brass, Steel

INSTALLATION DIMENSIONS



() Parentheses = Millimeters



HOW TO ORDER

Size	NPTF Thread	
	Brass	Steel
1/4"	GS20B	GS20S

Pneutrol International Limited

UK Office 5 Caulside Drive, Antrim, BT41 2DU United Kingdom TEL: +44 (0) 28 9448 1800 www.pneutrol.com/industrialspares sales@pneutrol.com

European Office Unit 6, Saint Anthony's Business Park, Ballymount Road, D22 VW95 Ireland TEL: +553 (0) 1 4373653 www.pneutrol.com/industrialspares